

# Giving Shape to Ideas



35 ppm B&W output speed to keep pace with growing document demands 1200 x 1200 dpi resolution for sharp, clear images

Instant-on fuser for fast warm-up and first-copy output times

Accepts 8.5" x 11" or 8.5" x 14" paper in weights from 16 lb bond to 43 lb cover stock

Outstanding envelope printing quality

Standard auto duplexing and auto blank page removal to save paper

Mobile printing support (AirPrint, NFC)

# zhub 3301P

MONOCHROME SINGLE FUNCTION PRINTER

printer





# DIZPUD 3301P MONOCHROME SINGLE FUNCTION PRINTER



Overview	
bizhub 3301P	For small businesses with large workloads, the bizhub 3301P
	outperforms ordinary desktop printers. You will have 35 ppm B&W
	output, 1200 x 1200 dpi resolution, standard auto duplexing and built-ir
	connectivity for network integration with office MFPs - a cost-effective
	solution for higher productivity.

System	Specificati	inns

System Specifications	
System memory	Standard/Max.: 128 MB
Interface	10BASE-T/100BASE-TX Ethernet, USB 2.0,
	IEEE 1284 Bidirectional Parallel
Network protocols	IPv4, IPv6, IPP, SNMP, HTTP, HTTPS
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60-163 gsm
Paper input capacity	Standard: 300 sheets / Max.: 850 sheets
Tray 1	250 sheets / 4" x 6" to 8.5" x 14" / 60-120 gsm
Tray 2 (optional)	250 or 550 sheets / 5.5" x 8.5" to 8.5" x 14" / 60-120 gsm
Manual bypass	50 sheets / 4" x 6" to 8.5" x 14" / custom paper sizes / 60-163 gsm
Automatic duplexing	8.5" x 11" to 8.5" x 14" / 60-90 gsm
Output capacity	Max.: 150 sheets
Print volume	Max.: 50,000 pages/month <sup>1</sup>
Toner lifetime	Up to 10,000 pages
Imaging unit lifetime	Up to 60,000 pages
Power consumption	100-127 V / 47-63 Hz, less than 900 W (system)
System dimensions	399 mm x 262 mm x 307 mm (15.7" x 10.3" x 12.1") (W x D x H)
System weight	Approx. 14 kg (30.9 lb)

# **Printer Specifications**

rinitei opetintations	
Printing process	Electrostatic laser
Print speed	Up to 35 ppm (Letter)
Autoduplex speed	Up to 30 ppm (Letter)
1st print out time	6.5 sec.
Print resolution	1200 x 1200 dpi
PDL	PCL 5/6 emulation, PostScript 3, XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2² / 2012² Macintosh OS X 10.x or later Linux AS/400 SAP
Printer fonts	89 PCL, 91 PostScript 3 Emulation Latin
Print functions	Duplex, n-up, watermark, electronic sorting

# **Options**

PF-P11 Paper tray	5.5" x 8.5" to 8.5" x 14" / custom paper sizes / 250 sheets / 60-120 gsm
PF-P12 Paper tray	5.5" x 8.5" to 8.5" x 14" / custom paper sizes / 550 sheets / 60-120 gsm
DK-P02 Copier desk	Provides storage space for print media, etc. / Adjustable to bring machine to working height with a variety of configurations
UK-P01 User flash	256 MB User flash for storing fonts, forms and macros or to save job account log
NC-P01 Wireless LAN	Wireless LAN to network connector
CS-1	Convenient stapling of up to 50 prints per set
Convenience stapler	

## **System Features**

Security	TCP/UDP port disabling, certificate management, SNMPv3, HTTPS server, SSL protocol, IEEE 802.1x support, SMTP authentication
Software	PageScope Net Care Device Manager

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.



KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 5875 Explorer Drive, Suite 100, Mississauga, ON L4W 0E1











<sup>&</sup>lt;sup>2</sup> Supports 64-bit version only.