

Giving Shape to Ideas





High-speed print/copy output: 60 ppm colour, 75 ppm B&W Standard dual scanning handles up to 180 originals per minute INFO-Palette display for instant access to more information Large 9" colour display with quick tablet-like interface Downloadable apps to improve your productivity Built-in $\mathsf{Emperon}^\mathsf{m}$ print system, universal printer drivers Simitri™ HD toner guarantees excellent print quality Scan-to-Email and FTP, Scan-to-Me, Scan-to-Home convenience 6,650-sheet capacity, tab printing support, carbon-copy printing Standard 250 GB HDD for on-board document storage Finishing options for 80-page booklet-making, up to 100-sheet stapling Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more Internal card reader and other advanced security options ISO 15408 and IEEE 2600.1 security standards PageScope® suite, optional voice guidance, PDF/A formatting Multiple i-Options to suit the needs of your workflow Fiery® image control option for graphics-intensive applications Low power consumption, eco-indicator to help cut costs **EPEAT Gold-certified** Mobile printing support (AirPrint, Google Cloud Print, NFC)

bizhub C754e

COLOUR HIGH-VOLUME MULTIFUNCTION PRINTER







bizhub C754e

Superior colour, spectacular speed and simple touch-and-swipe operation make the bizhub C754e an ideal document solution for high-volume applications. Output of 60 ppm in colour and 75 ppm in B&W keeps work flowing – and you will have powerful, scalable options to increase your productivity and help control your costs.

System Overview

System Overview	
System memory	2,048 MB
System hard disk	250 GB
Interface	10BASE-T/100BASE-TX/1000BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 150 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes
	Banner paper: 11.75" x 47.25" max.
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3	1,500 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
Tray 4	1,000 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-301 (optional)	0,000 311000 7 0.0 X 11 7 02 200 goill
Large capacity tray LU-204 (optional)	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, punch, post insertion, z-fold, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1000 sheets
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray), unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output	Max.: 100 sheets (tray), unlimited
capacity	
Copy/print volume	Max.: 278,000 pages/month ¹
Toner lifetime	Black: 47,200 pages / CMY: 31,500 pages
Imaging unit lifetime	Black: 300,000 pages / 1,200,000 pages (Drum / Developer) CMY: 155,000 pages
Power consumption	120 V / 50/60 Hz, less than 2.1 kW (system)
System dimensions	25.5" x 31.5" x 45.5" (W x D x H)
System weight	Approx. 487.25 lb

				ca		

Copying process	Electrostatic laser copy, tandem, indirect			
Toner system	Simitri™ HD Polymerized Toner			
Print speed (8.5" x 11")	B&W: Up to 75 ppm (Portrait) / Colour: Up to 60 ppm (Portrait)			
Print speed (11" x 17")	B&W: Up to 37 ppm (Portrait) / Colour: Up to 30 ppm (Portrait)			
Autoduplex speed	B&W: Up to 75 ppm (Portrait) / Colour: Up to 60 ppm (Portrait)			
(8.5" x 11")				
1st copy out time	B&W: 3.6 sec. / Colour: 5.3 sec.			
Warm-up time	Approx. 22 sec. ²			
Copy resolution	600 x 600 dpi			
Gradations	256 gradations			
Multi-copy	1-9,999			
Original format	Up to 11" x 17"			
Magnification	25-400% in 0.1% steps, auto zooming			
Copy functions	Chapter, cover and page insertion, proof copy (print and screen), adjustment test print, digital art functions, job setting memory, poster mode, image repeat, overlay (optional), stamping, copy protection			

Printer Specifications

Print resolution	1800 x 600 dpi, 1200 x 1200 dpi
PDL	PCL 6 (XL 3.0), PCL 5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 / 2012 ³ Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Printer Specifications (optional)

Print controller	Embedded Fiery IC-414
Memory / HDD	2 GB / 160 GB
PDL	PostScript 3 (ver. 3019) PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.2.8 or later

Scanner Specifications

Scan speed	B&W / Colour: up to 180 opm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)	
Transmission	Analog, i-Fax, Colour i-Fax, IP-fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to	

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages	
Type of user boxes	Public	
	Personal (with password or authentication)	
	Group (with authentication)	
Type of system boxes	Secure Print, Encrypted PDF, Fax receipt, Fax polling, Annotation	
User box functionality	Reprint, combination, download, sending (email/FTP/SMB and fax), copy box to box	

	Fea	

Security	ISO 15408 EAL3				
	IEEE 2600.1				
	IP filtering and port blocking				
	SSL2, SSL3 and TSL1.0 network communication				
	IPsec support				
	IEEE 802.1x support				
	User authentication				
	Authentication log				
	Secure print				
	Hard disk overwrite (8 standard types)				
	Hard disk data encryption (AES 128)				
	Memory data auto deletion				
	Confidential fax receipt				
	Print user data encryption				
	Copy protection (Copy Guard, Password Copy) optional				
Accounting	Up to 1,000 user accounts				
	Active Directory support				
	(user name + password + email + SMB folder)				
	User function access definition				
	Optional Biometric authentication (finger vein scanner)				
	Optional ID card authentication (ID card reader)				
Software	PageScope Net Care Device Manager				
	PageScope Data Administrator				
	PageScope Box Operator				
	PageScope Direct Print				
	Print Status Notifier				
	Driver Packaging Utility				
	Log Management Utility				

Log wariagement during

"Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.

This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

2 Warm-up time may vary depending on the operating environment and usage.

3 Supports x64 only.

Components and Options

Components and Options	8
AU-102 Biometric	Finger vein scanner
authentication	
EK-604 USB I/F kit	USB keyboard connection
EK-605 USB I/F kit	USB keyboard connection, Bluetooth
FK-508 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FK-511 Fax board	Super G3 fax, digital fax functionality
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output
FS-535 Staple finisher	
<u> </u>	100-sheet stapling, 3,200 sheets max. output
IC-414 Fiery controller	Professional colour print controller
ID card reader	Various ID card technologies
JS-602 Job separator	Separation for fax output, etc.
for FS-535	
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-101 v3	Web browser
Web browser	
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3	Provides voice guidance functions
Voice guidance	
LK-105 v3	Searchable PDF
OCR text recognition	
LK-106	Supports native barcode printing
Barcode fonts	
LK-107	Supports native Unicode printing
Unicode fonts	
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 Enhanced	Generates various file formats including DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LU-204	8.5" x 11" to 12" x 18", 2,500 sheets, 52-256 gsm
Large capacity tray	
LU-301	8.5" x 11", 3,000 sheets, 52-256 gsm
Large capacity tray	
MK-728 Mount kit	Installation kit for FK-508 fax board
MK-735 Mount kit	Installation kit for ID card reader
OT-503 Output tray	Output tray used instead of finisher
PI-505 Post inserter	Cover insertion, post finishing
for FS-535	
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-534	
PK-521 Punch kit	2/3-hole punching, autoswitching
for FS-535	
SC-508 Security kit	Copy Guard function (2x required)
SD-512 Saddle stitch	Booklet finishing, half-fold, tri-fold
kit for FS-535	Doordor milorality, real role, ar role
SX-4600WAN	Wireless LAN to network connector
Wireless LAN	Throise E in to noth of note.
UK-204	Memory extension for i-Options
i-Option memory	Mornory extension for a options
VI-506 Interface kit	Fiery controller interface card
for IC-414	Tiony defination interface out a
WT-506 Working table	Authentication device placement
ZU-606 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching
for FS-535	Z-10iu 10i 11 x 17 pilitis, Z/3-110le pullulling
101 1 0-303	





KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 5875 Explorer Drive, Suite 100, Mississauga, ON L4W 0E1











© 2014 KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, Count on Konica Minolta, bizhub, PageScope, and Giving Shape to Ideas are registered trademarks or trademarks of KONICA MINOLTA, INC. Trademarks of the Canadian Breast Cancer Foundation, used under licence. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design and specifications are subject to change without notice.