

Giving Shape to Ideas







bizhub C554e

Ideal for high-speed colour output and fast scanning to multiple destinations, the bizhub C554e can power up your workflow with 55 ppm output in both colour and B&W, enhanced touchscreen convenience and multiple finishing options for creating high-impact colour documents in-house.

System Overview

System Overview	
System memory	2,048 MB
System hard disk	250 GB
Interface	10BASE-T/100BASE-TX/1000BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
Drintable nener weight	Banner paper: 11.75" x 47.25" max.
Printable paper weight Paper input capacity	52-300 gsm
	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm 500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 2	
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Large capacity tray PC-410 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray LU-301 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray LU-204 (optional)	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, punch, post-insertion, z-fold, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1000 sheets
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray), unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray), unlimited
Copy/print volume	Max.: 200,000 pages/month ¹
Toner lifetime	Black: 27,000 pages / CMY: 26,000 pages
Imaging unit lifetime	Black: 135,000 pages / 590,000 pages (Drum / Developer) CMY: 95,000 pages
Power consumption	120 V / 50/60 Hz, less than 1.92 kW (system)
System dimensions	24.2" x 27" x 36.3" (W x D x H)
System weight	Approx. 220.5 lb
,	

Copier	Specif	ications

Copying process	Electrostatic laser copy, tandem, indirect	
Toner system	Simitri™ HD Polymerized Toner	
Print speed (8.5" x 11")	B&W / Colour: up to 55 ppm (Portrait)	
Print speed (11" x 17")	B&W / Colour: up to 27 ppm (Portrait)	
Autoduplex speed (8.5" x 11")	B&W / Colour: up to 55 ppm (Portrait)	
1st copy out time	B&W: 4.1 sec. / Colour: 4.6 sec.	
Warm-up time	Approx. 22 sec. ²	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Copy functions	Chapter, cover and page insertion, proof copy (print and screen), adjustment test print, digital art functions, job setting memory, poster mode, image repeat, overlay (optional), stamping, copy protection	

Printer Specifications

Print resolution	1800 x 600 dpi, 1200 x 1200 dpi
PDL PCL 6 (XL 3.0), PCL 5c, PostScript 3 (ver. 3016), XPS	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Printer Specifications (optional)

Print controller	Embedded Fiery IC-414	
Memory / HDD 2 GB / 160 GB		
PDL	PostScript 3 (ver. 3019) PCL 6/5c	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.2.8 or later	

Scanner Specifications

oouimor opoomounor	
Scan speed	B&W / Colour: up to 160 opm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)	
Transmission	Analog, i-Fax, Colour i-Fax, IP-fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to	

User Box Specifications

ooo. Don opoomounom		
Storable documents	Max.: 3,000 documents or 10,000 pages	
Type of user boxes	Public	
	Personal (with password or authentication)	
	Group (with authentication)	
Type of system boxes	Secure Print, Encrypted PDF, Fax receipt, Fax polling, Annotation	
User box functionality	Reprint, combination, download, sending (email/FTP/SMB and fax), copy box to box	

Syste	

Security	ISO 15408 EAL
	IEEE 2600.1
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
1 This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.
2 Warm-up time may vary depending on the operating environment and usage.
3 Supports x64 only.

Components and Options

Components and Option	S
AU-102 Biometric	Finger vein scanner
authentication	1001
EK-606 USB I/F kit	USB keyboard connection
EK-607 USB I/F kit	USB keyboard connection, Bluetooth
DK-510 Copier desk	Provides storage space for print media and other materials
FK-508 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FK-511 Fax board	Super G3 fax, digital fax functionality
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511 Booklet finisher	50-sheet staple finisher, 20-sheet booklet finisher, 3,300 sheets max. output
FS-535 Staple finisher	100-sheet stapling, 3,200 sheets max. output
IC-414 Fiery controller	Professional colour print controller
ID card reader	Various ID card technologies
JS-506 Job separator	Separation for fax output, etc.
JS-602 Job separator	Separation for fax output, etc.
for FS-535	Separation for fax output, etc.
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-101 v3	Web browser
Web browser	
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3	Provides voice guidance functions
Voice guidance	
LK-105 v3	Searchable PDF
OCR text recognition	Companies and the bound of the companies
LK-106 Barcode fonts	Supports native barcode printing
LK-107	Supports native Unicode printing
Unicode fonts	Supports flative officode printing
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 Enhanced	Generates various file formats including DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LU-204	8.5" x 11" to 12" x 18", 2,500 sheets, 52-256 gsm
Large capacity tray	
LU-301	8.5" x 11", 3,000 sheets, 52-256 gsm
Large capacity tray MK-728 Mount kit	Installation kit for FK-508 fax board
MK-735 Mount kit	Installation kit for ID card reader
OT-506 Output tray	Output tray used instead of finisher
PC-110	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
Universal tray (x1)	3.5 x 6.5 to 11 x 17 , 500 shoots, 52-250 gsin
PC-210	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2)	,
PC-410	8.5" x 11", 2,500 sheets, 52-256 gsm
Large capacity tray	
PI-505 Post inserter	Cover insertion, post finishing
for FS-535	0/01
PK-519 Punch kit	2/3-hole punching, autoswitching
for FS-533	2/2 hala punahing autoquitahing
PK-520 Punch kit for FS-534	2/3-hole punching, autoswitching
PK-521 Punch kit	2/3-hole punching, autoswitching
for FS-535	20 note partorning, autoomitering
SC-508 Security kit	Copy Guard function (2x required)
SD-512 Saddle stitch	Booklet finishing, half-fold, tri-fold
kit for FS-535	
UK-204	Memory extension for i-Options
i-Option memory	
UK-208 Wireless LAN	Wireless LAN to network connector
VI-506 Interface kit	Fiery controller interface card
for IC-414	
WT-506 Working table	Authentication device placement
ZU-606 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching
for FS-535	



KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 369 Britannia Road East, Mississauga, ON L4Z 2H5











