

TECHNOLOGY



# AccurioPress 6136

## MONOCHROME DIGITAL PRODUCTION PRESS/COPIER/COLOUR SCANNER

136 ppm output for high-volume monochrome print production

Inline, closed loop quality management system

High-speed dual colour scanning at 240 ipm

Job ticket and page editing from 15" touch-screen display for easy on-board press control Color Centro and Hot Folder capabilities for job management and workflow

True 1200 x 1200 dpi resolution with enhanced screening technologies for sharpness

Duty cycle 3,240,000 — accepts media up to 350 gsm

Reliable air-suction paper feed option for smooth paper feeding

Professional feeding of coated media and envelopes

18,000-sheet maximum paper capacity with options

Humidifier option removes static, reduces paper curl

Saddle-stitched booklets with three-side trim and square-fold

Produce 600-page perfect bound books and up to 100-sheet stapling

Envelope print support with optional fuser

Innovative GBC punch unit with interchangeable die sets

Built-in print controller with PCL, PostScript, TIFF and PDF

 $\label{eq:simitri} \textbf{Simitri}^* \, \textbf{HD} \, \textbf{toner} \, \textbf{with biomass to protect the environment}$ 

EPEAT Gold-certified and ENERGY STAR compliant

## **AccurioPress 6136**

## MONOCHROME DIGITAL PRODUCTION PRESS / COPIER / COLOUR SCANNER

The AccurioPress 6136 redefines the way you think about monochrome printing, delivering high-quality black and white prints in high-volume environments. Exceptional speed and versatility with 136 ppm print/copy output combined with an aggressive monthly duty cycle of over three million impressions, real-time automated density and registration adjustments to produce unmatched print quality.

#### SYSTEM SDECIEICATIONS

SYSTEM SPECIFICATIONS	
Resolution	<b>Print:</b> 1200 x 1200 dpi
	<b>Scan:</b> 600 x 600 dpi
Paper weight	Standard: 40–300 gsm
	Opt.: PF-710, PF-709 (middle tray): 40–350 gsm
Auto duplex	40-300 gsm
Paper sizes (max.)	324 x 463 mm (12.76" x 18.23")
	<b>Opt.:</b> PF-709: 324 x 463 mm (12.76" x 18.23")
	PF-710: 324 x 483 mm (12.76" x 19.02")
Paper sizes (min.)	182 x 139 mm (7.17" x 5.47")
	<b>Opt.:</b> PF-709: 95 x 139 mm (3.74" x 5.47")
	PF-710: 95 x 133 mm (3.74" x 5.24")
Image loss (max.)	3.0 mm or less for top edge
	2.0 mm or less for bottom edge
	2.0 mm or less for right/left edges
Warm-up time	420 seconds or less
Paper input capacity	Standard: 3,000 sheets
	Max.: 18,000 sheets
Main unit dimensions	39" x 35.8" x 57"
(W x D x H)	
Main unit weight	813.5 lb
Power requirements	208 VAC to 240 VAC, 20 A, 60 Hz

#### **PRODUCTIVITY**

8.5" x 11" (max. per minute)	136 ppm	
Monthly duty cycle (max.)	3,240,000 pages	

## **CONTROLLER**

Туре	Embedded (network standard)
СРИ	Intel i5-4570S 2.9 GHz
Memory	16 GB
HDD/SSD	HDD: 1-TB x2, SSD: 4 GB
Print-description language	PCL SE/XL (PCL 6), Adobe PostScript 3 (PS3020),
	PDF v1.7, TIFF v6, PPML v2.2, APPE 4.2 (with UK-217)
Printing method	TCP/IP (LPR, RAW socket), NetBEUI, IPP, WSD, Bonjour, SMB
Applicable OS	PCL, PS, PS Plug-in:
•	Windows 7*1/8.1*1/10*1
	Windows Server 2008/2008 R2/2012/2012 R2/2016
	Mac OS X 10.8/10.9/10.10/10.11/10.12
Interface	10/100/1000BASE-T, USB 3.0 host, USB 2.0 device
the talk waster to	

<sup>\*1</sup> Including 64-bit versions.

#### **SCANNER SPECIFICATIONS**

Туре	Full colour
Scan speed (8.5" x 11")	Single-sided 120 ipm/duplex 240 ipm
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-HDD, Scan-to-FTP, Scan-to-SMB, Scan-to-Email,
	Scan-to-WebDAV, Scan-to-USB
Scan formats	TIFF, PDF, Encrypted PDF, PDF/A-1a, PDF/A-1b, Compact PDF,
	IPEG, XPS

## **COPIER SPECIFICATIONS**

Gradations	256 gradations
First copy out <sup>1</sup>	2.7 seconds or less
Continuous print speed <sup>2</sup>	136 pages/min (letter landscape)
Magnification	25–400% in 0.1% steps

When letter landscape original is scanned on the platen (zoom 100%, Tray-1).

### **OPTIONS**

CR-101	Creaser unit for SD-513
EF-105	Envelope fuser
FA-503	PFU adjustment kit
FD-503	Multi-fold punch unit
FD-504	Square folding unit
	for SD-513
FS-532	100-sheet staple finisher
FS-532 PK/SD	100-sheet staple finisher
	with PK and SD-510-522
Punch G2	GBC advanced
	multi-punching unit
GP-501	GBC multi-hole punch unit
GP-502	GBC inline ring
	binding unit
HD-523	Inner HDD kit
HM-103	Humidification unit
	for RU-518
HT-506	Dehumidification heating
	unit for PF-710
IQ-501	Intelligent quality optimizer
LC-501	Cart for LS-506
LS-506	Stacking unit

MK-732	Post-inserter mount kit
	for FS-532
MK-737	Mount kit for
	third-party products
OT-510	Open stacker
PB-503	Perfect binder
PF-709	Friction paper feed unit
	with air assist
PP-701	Preprinted paper kit
	for PF-709
PF-710	Vacuum paper feed unit
PI-502	Post inserter for FS-532
PK-522	2/3-hole punch for FS-532
RH-101	Removable HDD kit
RU-510	Relay unit for GP-501
RU-518	Relay unit for de-curling
SD-506	Booklet-making unit
SD-510	Saddle-stitch kit for FS-532
SD-513	Saddle-stitch unit
SD-513/F	Saddle-stitcher front
TU-503	Trimmer unit for SD-513





For complete information on Konica Minolta products and solutions, please visit: www.konicaminolta.ca

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA and the KONICA MINOLTA logo are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design and specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 5875 Explorer Drive, Mississauga, ON L4W 0E1





<sup>&</sup>lt;sup>2</sup> Print speed may vary depending on paper type.